

CABLOTECH
Automation & Lighting



LINEAR ECO



La serie di apparecchi illuminanti a LED LINEAR ECO nasce per soddisfare le esigenze di illuminazione lineare nei contesti industriali, come ad esempio linee di produzione, sui banchi di lavoro, in magazzini bassi, cunicoli, corridoi e ovunque sia necessaria una illuminazione semplice ma efficace. Il corpo della lampada è realizzato in policarbonato che rende la lampada resistente e durevole nel tempo. La struttura è completata da staffe e ganci per il fissaggio a soffitto o tramite catenella. La sorgente LED è costituita da LED ad alta efficienza e con binning selezionato (Mac Adam Step 3), per garantire sempre la stessa gradazione di colore e qualità della luce. È possibile inoltre abbinare alla lampada il modulo con batterie per l'illuminazione di emergenza. Il grado di protezione dell'apparecchio è IP66. Il prodotto è MADE IN ITALY e garantito 2 anni.

The LINEAR ECO LED light is designed to meet the needs of linear lighting in industrial contexts, such as production lines, work benches, low warehouses, tunnels, corridors and wherever simple but effective lighting is required. The body of the lamp is made of polycarbonate and this makes the lamp durable. The structure is completed by brackets and hooks for fixing to the ceiling or by chain. The LED source is made up of high efficiency LED with selected binning (Mac Adam Step 3), that always guarantee the same colour grade and quality of light. It is also possible to combine the lamp with the emergency lighting battery kit. The protection degree of the appliance is IP66. The product is MADE IN ITALY and guaranteed for 2 years.

Made in Italy



CODICE / CODE	LC0252 LINEAR PC 20 ECO 600mm	LC0240 LINEAR PC 40 ECO 1200 mm	LC0251 LINEAR PC 50 ECO 1500mm
ALIMENTAZIONE POWER SUPPLY	198-264Vac / 50-60Hz		
POTENZA MASSIMA ASSORBITA MAXIMUM POWER INPUT	20W	40W	50W
SORGENTE SOURCE	LED SMD		
TEMPERATURA COLORE COLOR TEMPERATURE	Cold White 5000K		
C.R.I.	min 80		
FLUSSO LUMINOSO NOMINALE RATED LUMINOUS FLUX	4.800 lm	6.400 lm	8.000 lm
FLUSSO LUMINOSO REALE ACTUAL LUMINOUS FLUX	2.400 lm	4.800 lm	6.000 lm
TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	Da/From -30°C a/to +40°C		
CONTROLLO CONTROL	On / Off		
MATERIALI MATERIALS	<ul style="list-style-type: none"> • Policarbonato (struttura) / <i>Polycarbonate (structure and screen)</i> • Pressacavi in plastica / <i>Plastic cable gland</i> • Silicone (guarnizioni) / <i>Silicone (gaskets)</i> 		
GRADO DI PROTEZIONE IP IP PROTECTION CLASS	IP66		
GRADO DI RESISTENZA AGLI URTI IK IK PROTECTION CLASS	IK10		
PESO WEIGHT	1,5 Kg	2,5 Kg	3,5 Kg
DIMENSIONI IMBALLO PACKAGING DIMENSIONS	700mm (L) x 100mm (W) x 120mm (H)	1300mm (L) x 100mm (W) x 120mm (H)	1600mm (L) x 100mm (W) x 120mm (H)
DIMENSIONE LAMPADA LAMP DIMENSION	662mm (L) x 95mm (W) x 111mm (H)	1272mm (L) x 95mm (W) x 111mm (H)	1572mm (L) x 95mm (W) x 111mm (H)
GARANZIA WARRANTY	2 Anni / 2 Years		



CABLOTECH srl

✉ Via Milano, 59
24040 Bonate Sopra (Bg) - Italia

T. +39 035 46 44 22
F. +39 035 49 43 275

info@cablotech.eu
@ www.cablotech.eu

in cooperation with

PROGTECH
Lighting